

Serial No. 10/509,516

REMARKS

The foregoing corrected sections, submitted in response to the Notice of Non-Compliant Amendment of June 1, 2005, properly includes the text of all pending claims, including withdrawn claims. Therefore, Applicants submit that the Amendment of January 12, 2005, is now in compliance with 37 CFR 1.121. No extension fee is due, since this paper is being submitted within one month of the mailing of the Notice of Non-Compliant Amendment.

Please charge any shortage in fees due in connection with the filing of this paper, including extension of time fees, to Deposit Account 500417 and please credit any excess fees to such deposit account.

Respectfully submitted,

McDERMOTT WILL & EMERY LLP



Richard E. Brown

Registration No. 47,453

600 13th Street, N.W.
Washington, DC 20005-3096
Phone: 202.756.8000 REB:lg
Facsimile: 202.756.8087
Date: June 14, 2005

**Please recognize our Customer No. 20277
as our correspondence address.**

Applicant: Mineki TAOKA, et al. Docket No. 70591-021

Title: PROJECTION TYPE VIDEO DISPLAY AND ILLUMINATING DEVICE Serial/Reg./Patent No. 10/509,516

Date Sent: 1/12/2005 ☒ Hand Carried ☐ Fax ☐ Electronic ☐ Cert. of Mailing ☐ First Class Mail ☐ Express Mail No. _____

☒ Transmittal Letter

New Patent App ☐ Utility ☐ Design ☐ Cont. ☐ CIP ☐ Div. ☐ PCT ☐ RCE ☐ Prov


☐ Other: _____

pages of Specification
pages of Claims
pages of Abstract
pages of Formal/Informal Drawings


- ☐ Small Entity ☐ Large Entity
☐ Declaration/Power of Attorney
☐ Recordation of Assignment/Security Agreement
☒ Information Disclosure Statement

Form PTO 1449
copies of cited references

- ☒ Preliminary Amendment
☐ Response to Missing Parts Notice
☐ Resp. to Notice to Correct App. Papers
☐ Certified Copy of Priority Doc.
☐ Claim for Convention Priority
☐ Response/Amendment to Office Action of _____
☐ Request for _____ month Extension of Time



- ☐ Letter submitting _____ pages of drawings
☐ Req. for Approval of Drawing Amendments
☐ Req. for Oral Hearing
☐ Not. of Appeal ☐ Appeal Brief ☐ Reply Brief
☐ Rule 312 Amendment/Letter
☐ Req. for Acknowledgement of Cited Art
☐ Issue Fee
☐ Publication Fee
☐ Req. for Certificate of Correction
☐ Maintenance Fee for _____ years after grant
☐ Fee Address Indication Form
☐ Terminal Disclaimer
☐ Petition to Commissioner
☐ Status Inquiry
☐ Other _____



Check for \$	<input type="checkbox"/> Charge Deposit Acct. 500417\$	0	Atty Init.	AJS	Tkpr. #	4236	Secy. or PL:	LGrant
--------------	--	---	------------	-----	---------	------	--------------	--------

CMS Descrip.: _____

THE PATENT AND TRADEMARK OFFICE DATE STAMPED HEREON IS ACKNOWLEDGEMENT THAT THE ITEMS, CHECKED ABOVE, WERE RECEIVED BY THE PTO ON THE DATE STAMPED.

Applicant: Mineki TAOKA, et al. Docket No. 70591-021

Docket No.: 70591-021

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

PATENT

In re Application of

Customer Number: 20277

Mineki TAOKA, et al.

Confirmation Number: Unknown

Application No.: 10/509,516

Group Art Unit: Not yet assigned

Filed: September 28, 2004

Examiner: Not yet assigned

For: PROJECTION TYPE VIDEO DISPLAY AND ILLUMINATING DEVICE

Mail Stop Amendment
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Dear Sir:

Transmitted herewith is an Amendment in the above-identified application.

☒
☐
☐

No additional fee is required.

Applicant is entitled to small entity status under 37 CFR 1.27

Also attached:

The fee has been calculated as shown below:

	NO. OF CLAIMS	HIGHEST PREVIOUSLY PAID FOR	EXTRA CLAIMS	RATE	FEE
Total Claims	43	49	0	\$50.00 =	\$0.00
Independent Claims	2	3	0	\$200.00 =	\$0.00
Multiple claims newly presented					\$0.00
Fee for extension of time					\$0.00
					\$0.00
Total of Above Calculations					\$0.00

☐ Please charge my Deposit Account No. 500417 in the amount of \$0.00. An additional copy of this transmittal sheet is submitted herewith.

☒ The Commissioner is hereby authorized to charge payment of any fees associated with this communication or credit any overpayment, to Deposit Account No. 500417, including any filing fees under 37 CFR 1.16 for presentation of extra claims and any patent application processing fees under 37 CFR 1.17.

Respectfully submitted,

MODERMOTT WILL & EMERY LLP

Arthur J. Steiner
Registration No. 26,106

600 13th Street, N.W.
Washington, DC 20005-3096
Phone: 202.756.8000 AJS:lg
Facsimile: 202.756.8087
Date: January 12, 2005

Please recognize our Customer No. 20277 as our
correspondence address.



Docket No.: 70591-021

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

Mineki TAOKA, et al.

Application No. 10/509,516:

Filed: September 28, 2004

Examiner: Not assigned

For: PROJECTION TYPE VIDEO DISPLAY AND ILLUMINATING DEVICE

PRELIMINARY AMENDMENT

Mail Stop Amendment
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

Prior to examination of the above-referenced application, please amend the application as follows:

IN THE SPECIFICATION:



Please replace the paragraph beginning on page 6, line 17 and ending on page 7, line 6 with the following amended paragraph:

A projection type video display according to the present invention is characterized by comprising light deflecting means for circularly deflecting, in receiving irradiated light and transmitting the received light, ~~transmitting and/or reflecting the received light~~, the light; color separating means for separating the light into lights in the three primary colors and respectively introducing the lights into three hold type display elements; projecting means for recombining image lights in the respective colors obtained through the hold type display elements and projecting the recombined image lights; and element driving means for feeding a pixel-driving signal to each of the hold type display elements, and characterized in that the amount of light which will be wasted in producing said circular deflection is reduced by utilizing at least one of the functions including condensing, more than twice reflecting, and refracting, and in that each of the lights in the respective colors condensed in smaller areas than those of the element are circularly scrolled on the hold type display elements.

Please replace the paragraph on page 9, line 22 with the following amended paragraph:

There may be provided a rod prism for introducing light emitted from a light source with



IN THE CLAIMS

1. (Currently amended) A projection type video display characterized by comprising:

light deflecting means for circularly deflecting, in receiving irradiated light and transmitting the received light, ~~transmitting or reflecting the received light,~~ the light;

color separating means for separating the light into lights in the three primary colors and respectively introducing the lights into three hold type display elements;

projecting means for recombining image lights in the respective colors obtained through the hold type display elements and projecting the recombined image lights; and

element driving means for feeding a pixel-driving signal to each of the hold type display elements, and in that

the amount of light which will be wasted in producing said circular deflection is reduced by utilizing at least one of the functions including condensing, more than twice reflecting, and refracting, and in that the lights in the respective colors condensed in smaller areas than those of the element are circularly scrolled on the hold type display elements.

2. (Original) The projection type video display according to claim 1, characterized in that

the element driving means starts to feed pixel-driving signals for the succeeding frame to

3. (Original) The projection type video display according to claim 2, characterized in that

the pixel-driving signal is fed at N times (N is an integer of 2 or more) of a frame rate, and the timing of illumination of a pixel is matched with the time when a response of the pixel is flattened out.

4. (Original) The projection type video display according to claim 3, characterized in that

a pixel-driving signal whose change is more greatly emphasized than a pixel-driving signal allowing a necessary response value of the pixel to be obtained is fed to the pixel, to compensate for delay.

5. (Original) The projection type video display according to claim 4, characterized by comprising

a table allowing data representing the pixel-driving signal whose change is emphasized by the final pixel value in the preceding frame and the current pixel value to be obtained.

6. (Currently amended) The projection type video display according to claim 1 any

7. (Original) The projection type video display according to claim 6, characterized in that

such control that the luminance value of the pixel determined by a response of the pixel and a period of light irradiation onto the pixel in a case where the difference occurs is matched with a predetermined luminance value in a case where no difference occurs is carried out.

8. (Original) The projection type video display according to claim 7, characterized in that

a value whose change is more greatly emphasized than the target value of the response of the pixel is set depending on the difference, to feed the pixel-driving signal.

9. (Original) The projection type video display according to claim 7, characterized in that

the timing of feeding of the pixel-driving signal is controlled depending on the difference.

10. (Currently amended) The projection type video display according to claim 1 ~~any one of claims 1 to 9~~, characterized by further comprising

a rod prism for introducing light emitted from a light source with a reflector ~~light source~~ and condensed into the light deflecting means.

12. (Currently amended) The projection type video display according to claim 1 ~~any one of claims 1 to 11~~, characterized in that

the light deflecting means is constructed by rotatably providing a lens array wheel having a plurality of functional units each composed of a convex lens arranged in a disc shape along its circumference.

13. (Currently amended) The projection type video display according to claim 1 ~~any one of claims 1 to 11~~, characterized in that

the light deflecting means is constructed by rotatably providing a prism.

14. (Currently amended) The projection type video display according to claim 1 ~~any one of claims 1 to 11~~, characterized in that

the light deflecting means is constructed by rotatably providing a disc member having a light transmitter formed in a spiral shape and having a reflecting surface in an area other than the light transmitter.

15. (Currently amended) The projection type video display according to claim 1 ~~any one of claims 1 to 11~~, characterized in that

16. (Currently amended) The projection type video display according to claim 10-~~or~~
11, characterized in that

the rod prism is folded such that the light entrance direction and the light exit direction
differ,

the light deflecting means is composed of a rotatable cylindrical member having light
transmitters and reflectors alternately formed repeatedly on its surface, and

the whole or a part of the rod prism is positioned inside the cylindrical member.

17. (Original) The projection type video display according to claim 14, characterized
in that

the disc member is inclined to the direction of light irradiation,

an auxiliary mirror is provided at a position where light from the reflecting surface of the
disc member is received, and

the light reflected from the auxiliary mirror is introduced into the light transmitter in the
disc member.

18. (Original) The projection type video display according to claim 17, characterized
in that

19. (Currently amended) The projection type video display according to claim 14,
~~17, or 18,~~ characterized in that

the light deflecting means comprises a single spiral light transmitter, and produces a
single scrolling light per rotation driving.

20. (Currently amended) The projection type video display according to claim 14, ~~17,~~
~~or 18,~~ characterized in that

the light deflecting means comprises at least two spiral light transmitters, and produces at
least two scrolling lights per rotation driving.

21. (Original) The projection type video display according to claim 19, characterized
in that

the light deflecting means is constructed by putting a first rotating disc having one spiral
light transmitter and a second rotating disc having a spiral light transmitter for adjustment
corresponding to the spiral light transmitter close together, and

there is further provided a width adjusting mechanism for changing and setting a relative
rotation angle between the first rotating disc and the second rotating disc around its rotation axis,
to adjust the width of the spiral light transmitter.

22. (Original) The projection type video display according to claim 21, characterized in that

the width adjustment mechanism comprises

means for forming a direct or indirect meshed state between the first rotating disc and the second rotating disc and releasing the meshed state, and

means for releasing the meshed state after stopping the rotation of the first rotating disc and the second rotating disc, to fix either one of the first rotating disc and the second rotating disc and rotate the other rotating disc.

23. (Original) The projection type video display according to claim 21, characterized in that

the width adjusting mechanism is composed of driving means for generating a relative rotation driving force between the first rotating disc and the second rotating disc while maintaining a state where the first rotating disc and the second rotating disc are together rotated.

24. (Original) The projection type video display according to claim 23, characterized in that

one of the rotating discs is provided with an actuator, and a rotation driving force is

25. (Original) The projection type video display according to claim 23, characterized in that

one of the rotating discs is provided with one constituent portion of a magnetic force actuator, and the other rotating disc is provided with the other constituent portion of the magnetic force actuator.

26. (Original) The projection type video display according to claim 20, characterized in that

the light deflecting means is constructed by putting a first rotating disc having at least two spiral light transmitters and a second rotating disc having a spiral light transmitter for adjustment corresponding to the spiral light transmitter close together, and

there is further provided a width adjusting mechanism for changing and setting a relative rotation angle between the first rotating disc and the second rotating disc around its rotation axis, to adjust the width of the spiral light transmitter.

27. (Original) The projection type video display according to claim 26, characterized in that

the width adjustment mechanism comprises

means for forming a direct or indirect meshed state between the first rotating disc and the

28. (Original) The projection type video display according to claim 26, characterized in that

the width adjusting mechanism is composed of driving means for generating a relative rotation driving force between the first rotating disc and the second rotating disc while maintaining a state where the first rotating disc and the second rotating disc are together rotated.

29. (Original) The projection type video display according to claim 28, characterized in that

one of the rotating discs is provided with an actuator, and a rotation driving force is applied to the other rotating disc from the actuator.

30. (Original) The projection type video display according to claim 28, characterized in that

one of the rotating discs is provided with one constituent portion of a magnetic force actuator, and the other rotating disc is provided with the other constituent portion of the magnetic force actuator.

31. (Currently amended) The projection type video display according to claim 1 ~~any one of claims 1 to 18, 20, or any one of claims 26 to 30~~, characterized in that

lights for each irradiation period of the scrolling light.

32. (Original) The projection type video display according to claim 31, characterized in that

there is provided means which receives the video signal to control the rotation driving of the light deflecting means in synchronization with a synchronizing signal in the video signal,

the video signal correcting means comprises a plurality of correction tables corresponding to at least the two scrolling lights,

the correction table is selected by phase information in the rotation of the light deflecting means, and

an address is generated on the basis of the synchronizing signal in the video signal, to read out correction data from the selected correction table.

33. (Original) The projection type video display according to claim 32, characterized by comprising

Image photographing means, and

means for producing a plurality of correction tables on the basis of luminance information in each area at the time of projecting a predetermined image on a screen obtained by the image photographing means and phase information in the rotation of the light deflecting means.

35. (Currently amended) The projection type video display according to claim 1~~any one of claims 1 to 34~~, characterized by comprising

means for driving a light source by a pulse which is synchronized with the video signal,
and

means for controlling the rotation driving of the light deflecting means in synchronization with the video signal.

36. (Original) The projection type video display according to claim 35, characterized by comprising

frequency multiplying circuit for converting the pulse into a positive number multiple of the synchronizing signal.

37. (Currently amended) The projection type video display according to claim 1~~any one of claims 1 to 36~~, characterized in that

the lights in the respective colors separated by the color separating means are introduced into the hold type elements in the respective colors in optical path lengths which are equal to one another.

38. (Original) The projection type video display according to claim 37, characterized

the optical path of the two lights and the optical path of the one light are symmetrical about the optical axis, and

one of the two lights is separated at a halfway portion on the optical path of the two lights and is introduced onto the optical axis.

39. (Original) The projection type video display according to claim 37, characterized by further comprising

optical means in a rectangular parallelepiped shape serving as means for recombining the image lights in the respective colors,

one surface of the optical means in a rectangular parallelepiped shape being a light exit surface, a surface oppositely facing the light exit surface being a light entrance surface at the center, and right and left surfaces thereof being light entrance surfaces on the right and left sides,

first color separating means for separating white light into lights having the two primary color components and a light having the other primary color component,

second color separating means for separating the lights having the two primary color components into two lights having the one primary color component, and

a double-face mirror arranged on the incident side of the hold type display element arranged on the light entrance surface at the center so as to be inclined at 45 degrees to its light incident optical axis, and in that

40. (Original) The projection type video display according to claim 39, characterized in that

the optical means in a rectangular parallelepiped shape, the hold type display element arranged on the light entrance surface at the center, the double-face mirror, and the first color separating means are arranged on one straight line.

41. (Original) The projection type video display according to claim 40, characterized in that

the light deflecting means is arranged with its optical axis matched with the straight line.

42. (Original) The projection type video display according to claim 40, characterized in that

the light deflecting means is provided with its optical axis crossing the straight line at right angles.

43. (Currently amended) The projection type video display according to claim 1 ~~any one of claims 1 to 42~~, characterized in that

the light deflecting means is arranged on the optical path of the light in each of the colors in the color separation optical system.

a rod prism in a folded type in which the light entrance direction and the light exit direction differ; and

a cylindrical member having light transmitters and reflectors alternately formed periodically on its surface,

the whole or a part of the rod prism is positioned inside the cylindrical member.


REMARKS

Applicants respectfully request entry of the above amendments to the specification and claims. Support for all amendments is found in the specification as originally filed.

Applicants note that the claim amendments presented herein have reduced the number of pending claims due to removal of multiple dependencies. Please credit any excess fees to Deposit Account 500417.

Respectfully submitted,

McDERMOTT WILL & EMERY LLP



Arthur J. Steiner
Registration No. 26,106

600 13th Street, N.W.
Washington, DC 20005-3096
Phone: 202.756.8000 REB:lg
Facsimile: 202.756.8087
Date: January 11, 2005

**Please recognize our Customer No. 20277
as our correspondence address.**